

e-STUDIO388CP

Datasheet

- > With a print speed of up to 38 pages per minute and a maximum of paper capacity of 1,451 sheets, this is printer is a reliable partner when it comes to increasing your productivity.
- > Brilliant colours and excellent image quality deliver impressive documents during each printing process and shows the professionalism of your company.
- > The coloured 10.9 cm (4.3") touch panel allows you quick access to your print jobs and allows you to change the settings if necessary.
- > Standard features such as power-saving modes or duplex printing can help to save resources.



The e-STUDIO388CP is a robust A4 colour printer with an impressive high quality document output. A resolution of up to 1,200 x 1,200 dpi provides a magnificent document output with crystal-clear images and ensures a consistent print quality - even with high-volume print jobs.

Mobile printing capabilities offer the flexibility that is required by today's modern businesses. Clever options and solutions make it possible to adapt this printing system to your own individual requirements and thus contribute to the increase of your productivity and the optimisation of workflows.

Taking care of the environment and its resources is part of the Toshiba philosophy - starting with the selection of the materials to the subject of recycling. Not surprisingly that the e-STUDIO388CP complies with the strictest environmental regulations. The energy saving modes and the duplex printing function help to protect resources and the environment.

SPECIFICATIONS

General

Print & Copy Speed	38 ppm
Warm-up Time	~ 15 seconds (from sleep mode)
Paper Size & Weight	Cassette: A6-A4/custom, 60-176 g/m ² Bypass: 76 x 127 mm - 216 x 356 mm, 60-176 g/m ²
Paper capacity	Cassette: 1x 250 sheets Max.: 1,451 sheets
Inner Output Tray	125-sheet capacity
Automatic Duplex	A4/custom, 60-105 g/m ²
Control Panel	10.9 cm (4.3") colour touch panel
Memory	Standard: 1 GB, 256 MB Flash Memory
Interface	10Base-T/100Base-TX/1000Base-T (incl. IPv6), High Speed USB 2.0, WLAN ¹⁾ (IEEE802.11 ac/a/b/g/n)
Dimension & Weight	442 x 421 x 308 mm (W x D x H), ~ 21.1 kg
Starter Kit	Toner and Imaging Unit

Print

Resolution	Max.: 1,200 x 1,200 dpi
First Print Output Time	~ 7 seconds
Page Description Language	PCL 6, PCL 5, PostScript 3 and PDF v1.7 emulation, XPS, PPDS
Supported Systems	Windows 10/8/8.1/7, Windows Server 2016/Server 2012/Server 2008 (32/64 bit), Windows Server 2012 R2/ Server 2008 R2 (64 bit), Mac OS X 10.6-10.13, Linux/Unix, Novell NetWare, Citrix, SAP
Mobile Printing	AirPrint, Mopria Print Service, Google Cloud Print
Print Functions	Universal Printer Driver, Print from USB, Multiple pages per sheet, Envelope printing

System & Security

Device Management	e-BRIDGE Fleet Management System ¹⁾
System Features	Energy saving modes, Automatic toner saturation/ colour calibration
Accounting & Security	Private print, IP address filter, Port filter, Support of SNMPv3, SSL and IPSec protocols, 802.1x authentication ¹⁾ , Operator panel lock ²⁾ , Disk wipe ²⁾

Options

550-SHEET DRAWER - KD-1063	1x cassette, 550-sheet capacity, A5-A4, 60-176 g/m ²
650-SHEET DUO-DRAWER - KD-1064	1x cassette, 550-sheet capacity, A5-A4, 60-176 g/m ² 1x bypass, 100-sheet capacity, A6-A4, 60-176 g/m ²
SWIVEL CABINET - MH-3100	
ADJUSTABLE PRINTER STAND - KK-3200	
USER FLASH MEMORY - GC-1420	
HARD DISK DRIVE - GE-1250	
WIRELESS LAN MODULE - GN-1170	
FORMS & BARCODE CARD - GB-2080LXK	
PRESCRIBE CARD - GB-2290LXK	

¹⁾ Optional

²⁾ Requires optional HDD



Toshiba Tec Germany Imaging Systems GmbH
Carl-Schurz-Str. 7
41460 Neuss
Germany

Telephone
+49 2131-1245-0

Website
www.toshibatec.eu

